UNCLASSIFIED. DISTRIBUTION STATEMENT A.
Approved for public release; unlimited public distribution.

TECHNOLOGY DRIVEN. WARFIGHTER FOCUSED.

ALTERNATIVE FUELS

Pat Muzzell,
Alternative Fuels Team Leader
June 11, 2009

Report Documentation Page

Form Approved
OMB No. 0704-0188

1. REPORT DATE	2. REPORT TYPE	3. DATES COVERED
11 JUN 2009	**N/A**	**-**

4. TITLE AND SUBTITLE	5a. CONTRACT NUMBER
Alternative Fuels	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	5d. PROJECT NUMBER
Pat Muzzell	5e. TASK NUMBER
	5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER
US Army RDECOM-TARDEC 6501 E 11 Mile Rd Warren, MI 48397-5000	**19948RC**
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
	TACOM/TARDEC
	11. SPONSOR/MONITOR'S REPORT NUMBER(S)
	19948RC

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release, distribution unlimited

13. SUPPLEMENTARY NOTES
The original document contains color images.

14. ABSTRACT

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			
unclassified	**unclassified**	**unclassified**	**SAR**	**21**	

Topics

- **Introduction**
  - Transportation Market Evolution
  - Tactical Mobility Fuel
- **Single Fuel in the Battlefield**
  - What is the Single Fuel?
  - Certification / Qualification Pipeline
  - DARPA Alternative Jet Fuels Program
- **Coordinating the Overall Alternative Fuel Qualification Process**
  - Tri-Service POL Users Group
  - Within Army
- **Alternative Fuels Qualification – Status**
- **Army Fuel Requirements and the JP-8 Spec**

Transportation Market Evolution

21st Century
Transportation market evolution continues, shaped by heightened concerns about energy security and the environment.

- **Alternative fuels desired in the jet/diesel fuel supply**
- **Changes in fuels supply driven by**
  - Legislation [EPAct 2005, EISA 2007], Exec Orders [EO 13423]
  - USAF Alternative Jet Fuels Program with goal to certify aircraft on alternative jet fuels by 2011
  - Commercial Aviation Alternative Fuels Initiative (CAAFI)
  - Various initiatives to manufacture alternative fuels from diverse sources
- **Army active in assessing emerging changes**
  - Tri-department coordination of alternative fuels qualification efforts

Tactical Mobility Fuel



Naval Research Advisory Committee Panel* Report (April 2006)

* Dr. Walt Bryzik panel member, Chief Scientist, (Ret) TARDEC



Liquid hydrocarbons – ideal fuel for tactical mobility

DOD SINGLE FUEL POLICY

AVIATION KEROSENE GRADE (JP-8)
MIL-DTL-83133

JP-8 (Jet A-1 plus additives) is the primary fuel used for both air and ground equipment in all theaters, overseas and Continental U.S.

- **Tactical vehicle** designs impose severe limitations on volume and weight
- **Energy density** is therefore the primary consideration for fuel
- **Hydrogen presently unsuitable** as a tactical mobility fuel
  - made from other fuels/resources
  - containment reduces energy density by 10-20X

What is the Single Fuel?

Biomass Energy (renewable)

Fossil Energy (large U.S. resource)

Petroleum Crude Oil (declining discovery / production)

Diverse energy sources



Petroleum based

Non-Petroleum based

Single Fuel in the Battlefield (SFB)*: Kerosene-type (jet) fuels, whether petroleum-based or not, allowed under specs for JP-8 / JP-5 / Jet A-1

Alternative jet, diesel fuels

- Produced for dual-use (military and commercial)
- Meet specs used by military
- Often blends with petroleum-based fuels

* SFB Policy allows diesel fuel in ground equipment when supplying jet fuel not practicable or cost effective

Alternative Fuels RDT&E:

- Expand technical database on alternative fuels
- Engage in specifications development for alternative fuels
- Qualify alternative fuels for use in Army tactical / combat equipment and systems



TARDEC Alternative Fuels Focus

Certification / Qualification Pipeline



DARPA Alternative Jet Fuels

- **Agricultural crop oils** (canola, jatropha, soy, palm, etc.)
  - University of North Dakota EERC
  - UOP
  - General Electric (GE)
  - Swedish Biofuels AB
- **Cellulosic and algal feedstocks** that are non-competitive with food material
  - General Atomics ($19.9M)
  - SAIC ($25M)
- Acceptable **coal-derived** fuels
  - $8.4M total
  - proposals due 02 Jun 2009



Can alternative jet fuels be made on large-scale and be cost competitive?

Coordinating Overall Process for Alternative Fuel Qualification

- **Tri-Service POL Users Group**
  - Developing DoD qualification process
    - Includes all stakeholders (e.g., aircraft, ground vehicles/GSE, infrastructure . . .), OEMs
    - Process specified and mandated for alt fuel producers independent of feedstock
    - Requires process be recognized by major fuel specifications, standard agreements
  - Synthetic fuels database populated (85%)
  - JP-8 specification FT wording coordinated
  - Continued liaison with DESC SynFuels Working Group
  - Shared Lessons Learned, data and resources

FY08 Focus

  - Conduct gap analysis – synfuel efforts, expand to biofuels, ID potential joint efforts
  - Increase visibility outside SCP world
  - More awareness needed that group exists, recognition as key OSD asset
  - Development of framework for DoD test and certification process

FY09 Challenges

- **Within Army**
  - Currently in evaluation phase (see process flow chart next slide)
  - Coordination with AMRDEC, need to expand to other key RDEC stakeholders

Alternative Fuel Evaluation & Approval (Notional Qualification Process)



Army Synfuel Blends* Qualification Process

← Develop data needed to assess fuel's suitability for use. → ← Build user knowledge of and confidence in use of fuel. →

Laboratory Evaluations | **Component Evaluations** | **System Evaluations** | **Demonstrations**

- **Completed**
  - Fuel chemical composition and properties
  - Materials compatibility evaluations
  - Fuel lubricity evaluations (rotary fuel injection pump)
  - Fuel blends studies
  - Limited component/engine/system testing (ground equipment)
- **In Progress**
  - Engine performance / durability testing (NATO test cycle)
  - Test track evaluation – HMMWV
  - Tactical wheeled vehicle (5x5) pilot field demo
  - Fuel lubricity evaluations (common rail injection system)
  - Cetane - Volatility window studies
- **Planned**
  - Component/engine/system testing and demos **(Army Aviation)**

* Synfuel Blends: blends of Fischer-Tropsch Synthetic Paraffinic Kerosene and JP-8 meeting MIL-DTL-83133F(JP-8 spec)

Properties of Synthetic Paraffinic Kerosene (SPK)

JP-8

Fischer-Tropsch (FT) SPK*



- Nothing in FT SPK that is not in JP-8
- Not all compounds in JP-8 are necessarily in FT SPK, results in some differences in fuel characteristics

Aromatics:
Lower fuel density and volumetric energy density, higher Cetane No., less solvency

Sulfur:
No exhaust SOx

Trace compounds:
Less inherent fuel lubricity

- Can impact component or engine performance and durability

*Synthetic-Paraffinic Kerosene:
Hydrocarbons distributed across the full jet fuel boiling range and having on whole properties suitable for use as an aviation fuel.

Fuel Blends Are Implementation Path

- **TARDEC elastomer compatibility evaluations* supported a "blends implementation path"**
- **Blends of up to 50% by volume FT SPK with JP-8**
  - Blends minimize/eliminate risk of fuel leaks due to change in fuel aromatic content
- **Other aspects supporting a blends implementation path**
  - Production capacity will build slowly
  - Lower energy density of FT SPK

***SAE Paper 2007-01-1453**



- Nitrile components swell in JP-8, then shrink when switched into FT SPK (FT "JP-8")
- O-ring shrinkage increases risk of sealing failures
- Using unaffected o-ring elastomers or FT SPK in blends with JP-8 are ways to reduce this risk

Blends Study

- **FT SPK/JP-8 Blend Properties**
  - Compared properties of blends with typical properties of JP-8 (CONUS, 2004)
  - Determined properties of blends (up to 50% FT SPK) generally fell within typical “property box” of JP-8
  - Study documented in **SAE Paper 2006-01-0702**
- **Follow-on study looked at typical JP-8 in use at five Army installations in CONUS**
  - Determined that at four of the five installations blends with the maximum reduction of 50% by volume petroleum content (JP-8) are possible
  - Study results documented in **2007 IASH Conference Poster** (see next slide)
    - International Association of the Stability, Handling and Use of Liquid Fuels (IASH)

Property Values of Synfuel Blends* Fit Within Range for JP-8

EXAMPLE: Volumetric Energy Density (see chart)

(1) JP-8 batches procured in 2007 worldwide, range and distribution, wt. mean.**

(2) Test fuels, GEP engine evaluation. JP-8 and synfuel blend

(3) Minimum shown is calculated from what is allowed by JP-8 spec. for minimum density and minimum net heat of combustion.



* Synfuel Blends: blends of Fischer-Tropsch Synthetic Paraffinic Kerosene and JP-8 meeting MIL-DTL-83133F(JP-8 spec)

** Calculated values; batches missing data not included

Lubricity Testing
TARDEC F&L Research Facility

- **Bench-top lubricity evaluations**
  - BOCLE, SLBOCLE, and HFRR battery
  - BOCLE indicated improved lubricity of FT fuel treated with CI/LI additive per QPL-25107



- **Rotary fuel injection pump test rig testing**
  - Showed FT IPK with lubricity improved to a level indicative of acceptable field performance
  - Both at min. and max. treat rates per QPL-25017
  - Results documented in **SAE Paper 2004-01-2961**

"Early Demo" – Tactical Generators
TARDEC F&L Research Facility

- **Objective:** Operate tactical equipment using 50:50 FT synthetic fuel blend
- **Test Protocol**
  - Three 10 kW generator sets
  - Gen sets "broken-in" using Ultra-Low Sulfur Diesel (ULSD)
  - Gen sets fueling during test, operating cycles (% of total time)
    - Gen sets #1 & # 3
      - 10% – ULSD
      - 45% – JP-8
      - 45% – 50:50 blend of FT SPK:JP-8
    - Gen set # 2
      - 100% – FT SPK
  - Tests conducted for 1000 hrs at 50% load
- **Some Results** (final report in DTIC)
  - No reliability issues encountered
  - Power generation unchanged for all fuel cases
  - Exhaust emission checked; NOx lower using fuel blend than for JP-8

TWV Pilot Field Demo
TARDEC F&L Research Facility

- **Determine effects of using fuel blend in a subset Army legacy ground vehicles**
- **Field demonstration fleet (variety of wheeled vehicles) at Ft. Bliss, TX**
  - (2) M998 HMMWV
  - (9) M925 A2 5-Ton truck
  - (10) M1075 LMTV
  - (10) M1083 A1 FMTV
  - (2) M1089 A1 FMTV
  - (1) M984 A1 HEMTT
  - (1) M978 HEMTT
  - (10) M915 A4 TRAC
  - Control vehicles of the same type, operated on JP-8 will be included
- **Data generation**
  - Monthly fleet performance monitoring and fuel analyses
  - Vehicle fuel injection systems pre-test inspections for operation / fuel leaks
  - Up to 10 fuel injection system (blend fueled vehicles) post-test inspections (or earlier if needed) to check operation / fuel leaks
- **No recordable issues to-date**
- **Field demo expected to finish in July 2009**

Army Fuel Requirements and the JP-8 Specification

- **Army started conversion from diesel fuel to Single Fuel in the Battlefield (SFB) in 1980s, implemented in 1988**
  - Done on "no-harm" premise basis for use of aviation turbine engine fuel in Army equipment typically having compression ignition (CI) engines
- **Army equipment has generally maintained acceptable levels of performance and durability using SFB, but have been some issues**
- **Requirements in diesel fuel specs not in JP-8 spec**
  - Minimum viscosity at 40°C (1.3 mm^2/s, No. 1-D)
    - Low fuel viscosity could lead to increased wear rates in some types of fuel injectors and injection pumps
  - Minimum Cetane No. (40, No. 1-D and 2-D)
    - Better cold-starting of CI engines
    - Better CI engine performance, namely less misfire/combustion instability, for light to medium load operation
  - Army request to add these two requirements, to Table A-1 for FT SPK, during last revision to MIL-DTL-83133F was dismissed, will try again for next revision
- **Different lubricity specification for DF-2 (HFRR) vs. JP-8**

BACK-UP SLIDES

What Are Biofuels?

"second generation"







"first generation"



Triglycerides (fats, oils)

pyrolysis

gasification
(or co-gasification
with coal)

"HRJ"

hydroprocessing

$CO + H_2$

"BTL"

alcohols

"direct fermentation"

jet fuel components

Courtesy AFRL,
Dr. Tim Edwards

HRJ Properties Study

- **HRJ properties indistinguishable from F-T SPK**
  - Spec properties (density, freeze, flash, heat of combustion, etc.)
  - Contaminants (metals, oxygenates, etc)
  - Fit-for-purpose properties (lubricity, dielectric, cetane, etc.) (in progress)
  - Combustion operability and emissions (in progress)
  - Material compatibility (in progress)
  - Blend properties (in progress)
- **Issues (same as SPK!)**
  - Density of blend
  - Aromatic content of blend
  - GHG footprint/sustainability
  - Cost (feedstock for HRJ, plant cost for F-T)

Courtesy AFRL,
Dr. Tim Edwards